



# AQC PARTS WASH

## INDUSTRIAL USAGE

### FREE OF PETROLEUM SOLVENTS & DYES

### PRODUCT DESCRIPTION

*AQC Parts Wash* is a low viscosity highly effective product for the removal of greases, oils, inks, water based paints and dirt. *AQC* Was formulated specifically to be used in heated wash sinks or tanks at 115 to 145 degrees F. This self-cleaning chemistry splits oils, greases and dirt so that they can be removed thus extending the chemistry life. *AQC* has been formulated to replace solvents for applications in manual parts washers.

### PRODUCT BENEFITS

- Safe for use with most metals, such as aluminum, steel, stainless steel, cast iron, copper and brass. *Aluminum parts should not be soaked for long periods of time with dissimilar metals, as some discoloration may result.*
- Frequently effective on such diverse materials as plastics, rubber products, and many synthetics.
- *AQC* incorporates a state-of-the-art rust inhibitor that leaves no measurable residue and will not interfere with painting.
- When heated to 115°F, *AQC* will outperform its hazardous counterparts on most oils and greases.
- The only evaporant is water. If water is replaced, and oils and greases removed, then the only reason to add chemistry is to compensate for the “carry out” of chemistry on the parts as they are removed.
- This aqueous-based solution has excellent rinsing characteristics that won’t interfere with painting or plating.
- Made with naturally occurring renewable resources and containing no petrochemicals or added dyes and fragrances, *AQC* is safe for use in closed environments and does not compromise indoor air quality.
- *AQC* is 100% biodegradable and an excellent tool for minimizing hazardous waste and reducing related costs, *provided no hazardous contaminants are added to the chemistry.*

## DIRECTIONS FOR USE

- Dilution rate: undiluted, up to 100:1.
- For most oils and greases, at 115°F, *AQC* will outperform its hazardous counterparts.
- For difficult to remove soils, the temperature can be increased incrementally, with the upper limit being 145°F.
- Significant performance gains can also be achieved by the use of automated equipment such as agitated tank washers and ultrasonic tanks.
- In most cases, the “*self cleaning*” characteristics of this product provide for *indefinite re-use* of this product as long as it is properly maintained and kept at the right concentration, i.e oil skimming and filtration.

## PRODUCT INGREDIENTS

Deionized water, nonionic surfactants, vegetable and oil seed (esters), EPA-registered microbiostat.

## FREE OF

Petrochemicals, D’Limonene or terpene products, volatile organic compounds, hazardous pH levels, dyes, or fragrances.

## SAFETY INFORMATION

See MSDS sheet:

- CAS #: 872-50-4 and CAS #: 141-43-5

## WARRANTY NOTICE

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond the purchase price as seller cannot control user’s handling and use, or effect of use.

## PACKAGING

- |  |   |
|--|---|
| <input type="checkbox"/> 1 gallon      | <input type="checkbox"/> 30 gallon drum |
| <input type="checkbox"/> 5 gallon pail | <input type="checkbox"/> 55 gallon drum |

## MANUFACTURED BY

BioForce Services • Minneapolis, MN 55413 • Phone (612) 302-3939  
Fax (612) 302-6935 • web address : [bioforceinc.com](http://bioforceinc.com) • email: [info@bioforceinc.com](mailto:info@bioforceinc.com)